

RECEIVED  
CENTRAL FAX CENTER

SEP 17 2007

## IN THE CLAIMS

1. (previously presented) A connection device for connecting a spinal fastener to an elongated member comprising:
  - a body having a first end, a second end, a first channel, a second channel, and a third channel, said body having a portion that tapers outwardly towards said second end;
  - a washer slidably mountable over said body, said washer having a substantially radial groove and an inner surface, wherein said inner surface has a diameter smaller than a diameter of the tapered portion of said body;
  - an offsetting member slidable over said first end; wherein said offsetting member contacts said spinal fastener in at least two locations; and
  - a fixation member insertable in said third channel, wherein the fixation member applies a compressive force preventing relative motion between the spinal fastener and the elongated member.
2. (original) The connection device as described in claim 1, wherein said offsetting member has a ring shape.
3. (original) The connection device as described in claim 2, wherein said offsetting member includes at least two differing inner diameters.
4. (original) The connection device as described in claim 3, wherein said offsetting member is composed of a shape memory alloy.
5. (original) The connection device as described in claim 4, wherein said offsetting member further includes at least one groove.

RESPONSE TO NON-FINAL OFFICE ACTION  
App. Ser. No. 10/824,752  
Atty. Dkt. No. 4002-1675  
Page 2 of 15

6. (previously presented) The connection device as described in claim 1, wherein said fixation member is a set screw, and said third channel is an aperture that is threaded and intersects said first channel.
7. (original) The connection device as described in claim 6, wherein said threaded aperture is arranged at an angle relative to a line between said first channel and said second channel.
8. (original) The connection device as described in claim 1, wherein said fastener is a spinal screw.
9. (original) The connection device as described in claim 1, wherein said fastener is a Schanz-type screw.
10. (currently amended) A method, comprising:
- connecting an elongated member to a connection member, said connection member having a first channel and a second channel, so that at least part of said elongated member occupies at least part of said first channel;
  - sliding an offsetting member over said connection device so that at least a part of said offsetting member is between at least a part of said first channel and at least a part of said second channel;
  - connecting a bone fixation member to said connection member so that at least part of said bone fixation member occupies at least part of said second channel; and
  - applying compressive force to said elongated member, said offsetting member, and said ~~spinal fastener~~ bone fixation member.

RESPONSE TO NON-FINAL OFFICE ACTION

App. Ser. No. 10/824,752

Atty. Dkt. No. 4002-1673

Page 3 of 15

wherein said offsetting member contacts said elongated member and said ~~spinal fastener~~  
bone fixation member in at least two differing locations.

11. (original) The method of claim 9, wherein said offsetting member has a ring shape.
12. (original) The method of claim 9, wherein said offsetting member further includes at least two differing inner diameters.
13. (original) The method of claim 9, wherein said offsetting member is composed of a shape memory alloy.
14. (original) The method of claim 9, wherein said offsetting member further includes at least one groove.
15. (original) A method, comprising:
  - providing a body having a first end, a second end, a first channel, a second channel, and an aperture, wherein a portion of said body tapers outwardly;
  - sliding a washer over said body;
  - passing a fastener through said body via said first channel; and
  - sliding an offsetting member over said body, wherein said offsetting member engages said fastener in at least two locations;
  - placing said body over said elongated member via said second channel; and
  - inserting a locking member into said aperture thereby locking said fastener with respect to said elongated member.

RESPONSE TO NON-FINAL OFFICE ACTION

App. Ser. No. 10/824,752

Atty. Dkt. No. 4002-1673

Page 4 of 15

16. (currently amended) The method of claim ~~15~~ 39, wherein said offsetting member has a ring shape.
17. (currently amended) The method of claim ~~15~~ 39, wherein said offsetting member further includes at least two differing inner diameters.
18. (original) The method of claim 15, wherein said offsetting member is composed of a shape memory alloy.
19. (currently amended) The method of claim ~~15~~ 39, wherein said offsetting member further includes at least one groove.
20. (currently amended) The method of claim ~~15~~ 39, wherein said locking member is a set screw, and said aperture is a threaded bore and intersects said second channel.
21. (original) The method of claim 20, wherein said threaded bore is arranged at an angle relative to a line between said first channel and said second channel.
22. (currently amended) An apparatus, comprising:  
a body member having a first channel and a second channel;  
an elongated member at least partially within said first channel;  
a bone fixation member at least partially within said second channel;  
an offsetting member slidably connected to said body member and positioned external to  
said body member and between said elongated member and said bone fixation member; and

RESPONSE TO NON-FINAL OFFICE ACTION

App. Ser. No. 10/824,752

Atty. Dkt. No. 4002-1675

Page 5 of 15

a washer having a substantially radial groove, said washer connected to said body so that said groove accommodates at least a portion of said bone fixation member.

23. (original) The apparatus of claim 22, wherein said offsetting member has a ring shape.
24. (original) The apparatus of claim 22, wherein said offsetting member further includes at least two differing inner diameters.
25. (original) The apparatus of claim 22, wherein said offsetting member is composed of a shape memory alloy.
26. (original) The apparatus of claim 22, wherein said offsetting member further includes at least one groove.
27. (original) The apparatus of claim 22, further comprising a locking member connected to said body.
28. (original) The apparatus of claim 27, wherein said locking member is a set screw.
29. (original) The apparatus of claim 28, wherein said body includes a threaded aperture enabling connection of said body to said locking member, said threaded aperture being arranged at an angle relative to a line between said first channel and said second channel.
30. (original) The apparatus of claim 22, wherein said elongated member is a spinal rod.

RESPONSE TO NON-FINAL OFFICE ACTION

App. Ser. No. 10/824,752

Atty. Dkt. No. 4002-1675

Page 6 of 15

31. (currently amended) The apparatus of claim 22 37, wherein said bone fixation member includes a threaded member.

32. (currently amended) The apparatus of claim 22 37, wherein said bone fixation member includes a hook.

33. (currently amended) The apparatus of claim 22 37, wherein said bone fixation member includes a clamp.

34. (currently amended) ~~The apparatus of claim 1~~ A connection device for connecting a spinal fastener to an elongated member comprising:

a body having a first end, a second end, a first channel, a second channel, and a third channel, said body having a portion that tapers outwardly towards said second end;

a washer slidably mountable over said body, said washer having a groove and an inner surface, wherein said inner surface has a diameter smaller than a diameter of the tapered portion of said body;

an offsetting member slidable over said first end, wherein said offsetting member contacts said spinal fastener in at least two locations; and

a fixation member insertable in said third channel, wherein the fixation member applies a compressive force preventing relative motion between the spinal fastener and the elongated member, wherein the entirety of said offsetting member is between a central longitudinal axis of the spinal fastener and a central longitudinal axis of the elongated member.

RESPONSE TO NON-FINAL OFFICE ACTION

App. Ser. No. 10/824,752

Atty. Dkt. No. 4002-1673

Page 7 of 15

35. (previously presented) The apparatus of claim 1, wherein a portion of said body extends through said offsetting member.

36. (cancelled)

37. (currently amended) ~~The apparatus of claim 22~~ An apparatus, comprising:  
a body member having a first channel and a second channel;  
an elongated member at least partially within said first channel;  
a bone fixation member at least partially within said second channel;  
an offsetting member slidably connected to said body member and positioned between  
said elongated member and said bone fixation member; and  
a washer having a groove, said washer connected to said body so that said groove  
accommodates at least a portion of said bone fixation member, wherein a portion of said body  
member extends through said offsetting member.

38. (cancelled)

39. (currently amended) ~~The method of claim 15~~ A method, comprising:  
providing a body having a first end, a second end, a first channel, a second channel, and  
an aperture, wherein a portion of said body tapers outwardly;  
sliding a washer over said body;  
passing a fastener through said body via said first channel; and  
sliding an offsetting member over said body, wherein said offsetting member engages  
said fastener in at least two locations;

RESPONSE TO NON-FINAL OFFICE ACTION  
App. Ser. No. 10/824,752  
Atty. Dkt. No. 4002-1675  
Page 8 of 15

placing said body over said elongated member via said second channel; and  
inserting a locking member into said aperture thereby locking said fastener with  
respect to said elongated member,

wherein said washer has an opening, and said sliding of said washer includes having said washer opening substantially perpendicular to said first channel.

40. (new) The apparatus of claim 37, wherein said offsetting member further includes at least two differing inner diameters.

41. (new) The apparatus of claim 37, wherein said offsetting member further includes at least one groove.

42. (new) The apparatus of claim 37, further comprising a locking member connected to said body.

43. (new) The apparatus of claim 42, wherein said locking member is a set screw.

44. (new) The apparatus of claim 37, wherein said body member has a flat surface on either side of said body member.

45. (new) The apparatus of claim 37, wherein said washer has a first outer surface and a second outer surface, said first outer surface having a diameter that is smaller than a diameter of said second outer surface.

RESPONSE TO NON-FINAL OFFICE ACTION

App. Ser. No. 10/824,752

Atty. Dkt. No. 4002-1675

Page 9 of 15



46. (new) The apparatus of claim 34, wherein said offsetting member further includes at least two differing inner diameters.

47. (new) The apparatus of claim 34, wherein said offsetting member further includes at least one groove.

48. (new) The apparatus of claim 34, wherein said fixation member is a set screw.

49. (new) The apparatus of claim 34, wherein said body member has a flat surface on either side of said body member.

50. (new) The apparatus of claim 34, wherein said washer has a first outer surface and a second outer surface, said first outer surface having a diameter that is smaller than a diameter of said second outer surface.

RESPONSE TO NON-FINAL OFFICE ACTION

App. Ser. No. 10/824,752

Atty. Dkt. No. 4002-1675

Page 10 of 15